

MEDIDERM® 3505

Medical Adhesive Laminate

Description

Closed-cell Polyolefin foam coated on one side with a high MVTR pressure-sensitive acrylic adhesive.

Characteristics

- Conformable
- Can be used with hydrophobic or hydrophilic pressure sensitive adhesives, PIB, silicone and acrylic based systems
- Available with a variety of release liners (paper, polyester, LDPE)
- Supported by Drug Master File (s).



Properties

Tests Performed


Typical Values

| | |
|--|-------|
| Adhesive Coat Weight (g/m ²) | 96 |
| Adhesion to Stainless Steel (g/inch) | 1,801 |
| Peel from Release Liner (g/2 inch) | 50 |
| Polyken Tack (g/cm ²) | 2507 |
| MVTR (g/m ² /day) | 41 |

Typical values are intended to be used as a guide and are not intended for specification purposes

Limited Warranty Statement on Reverse

Construction



Ordering Information

| | |
|----------------|--------------------------------------|
| Width | Maximum 43 inches |
| Diameter | Maximum 20 inches |
| Length | Maximum 1,000 feet |
| Safety Testing | Consistent with intended application |
| Storage | Temperature 50-80°F; Humidity 40-60% |

Limited Warranty and Conditions— Please Read Carefully

Mylan believes the information in this publication is an accurate description of the typical; characteristics and/or uses of the product(s). It is the purchaser's responsibility to thoroughly test the product in the purchaser's specific application to determine its performance, efficacy and safety, especially in light of any third party intellectual property rights. Suggestions of uses should not be taken as inducements to infringe any particular patent or other protected proprietary rights.

Unless Mylan provides you with a separate specific written warranty of fitness for a particular use, Mylan's sole warranty is that the product(s) as supplied, will meet Mylan's then current sales specification. MYLAN SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR USE. Your exclusive remedy and Mylan's sole liability for breach of warranty is limited to refund of the purchase price or replacement of any Mylan product shown to be other than as warranted, and Mylan expressly disclaims any liability for incidental or consequential damages.

Applicable test methods and product specifications available upon request.